TECHNICAL PARAMETERS FOR SOLID FUEL LOCAL SPACE HEATERS EU 2015/1185 OF 24. APRIL 2015

Model identifier(s): Scan 5003-S FL	
Indirect heating functionality	No
Direct heat output(kW)	5.7
Indirect heat output(kW)	N.A

						Emissions from space heating at nominal heat output			
				Preferred fuel	Model	PM	OGC	CO	NO _x
Fuel				(Only one)	identifier(s)	[X] mg/N	lm₃ (13 '	% 0 ₂)	
Wood logs with moisture of	content ← 25	5%		Yes	No	11	53	940	118
Compressed wood with moisture content < 12%				No	No				
Other woody biomass				No	No				
Anthracite and dry steam coal				No	No				
Hard coke				No	No				
Low temperature coke				No	No				
Bituminous coal				No	No				
Lignite briquettes				No	No				
Peat briquettes				No	No				
Blended fossil fuel briquettes				No	No				
Other fossil fuel				No	No				
Blended biomass and fossil fuel briquettes			No	No					
Other blend of biomass and solid fuel			No	No					
Characteristics when op	erating with	the prefer	red fuel						
Seasonal space heating er	nergy efficie	ncyη _s [%]		75					
Energy Efficiency Class			A+						
Energy Efficiency Index (E	nergy Efficiency Index (EEI)			113					
ltem	Symbol	Value	Unit	ltem		Symbo	bl \	/alue	Unit
Heat output				Use efficie	ency (NCV as re	ceived)			
Nominal heat output	P _{nom}	5.7	kW	Useful efficient nominal head		$\eta_{\rm th,nom}$		85	%
Minimum heat output (indicative)	P_{min}	N.A.	kW	minimum h	Jseful efficiency at ninimum heat output (indicative)			N.A.	%
Auxiliary electricity con	sumption			Type of he	at output/roo	m tempe	rature	control (select or
At nominal heat output	el _{max}	x,xxx	kW	single stage heat output, no room temperature control			[y	es/no]	
At minimum heat output	el _{min}	x,xxx	kW	two or more manual stages, no room temperature control			[y	es/no]	Yes
In standby mode	el _{sB}	x,xxx	kW	with mechanic thermostat room temperature control			[y	es/no]	
				with electronic room temperature control			[y	es/no]	
				with electronic room temperature control plus day timer			[y	es/no]	
				with electronic room temperature control plus week timer			-,	es/no]	
					Other control options (multiple select			possible)	
				room temperature control, with presence detection			[y	es/no]	
				room temperature control, with open window detection				es/no]	
				with distan	with distance control option			es/no]	
Permanent pilot flame p	ower requir	ement							
Pilot flame power requirement (if applicable)	P_{pilot}	N.A.	kW				\int		
Contact details	Name and a	address of tl	he supplier:		Brian Ørum, R&I	Manager So	″ ″∠, an A/S De	nmark	